

Use Case



- Deliver the data from each line to 12 FPGA boards
- Enable each FPGA board to send data to any line
- At least 312 (?!) 10G links: 24 + 24*12 = 312



• 12x SFP+ ports for exchange connectivity

 24x QSFPDD ports (12 port pairs) for downstream (FPGA board) connectivity

 6x QSFPDD ports for housekeeping/management tasks or external timestamping/capture






• 12x SFP+ ports for exchange connectivity

 24x QSFPDD ports (12 port pairs) for downstream (FPGA board) connectivity

 6x QSFPDD ports for housekeeping/management tasks or external timestamping/capture

Configurable Layer 1 for SFP+ output




12x SFP+ ports for exchange connectivity

 24x QSFPDD ports (12 port pairs) for downstream (FPGA board) connectivity

 6x QSFPDD ports for housekeeping/management tasks or external timestamping/capture

Configurable Layer 1 for SFP+ output

Downstream interconnect with 2"-7"
QSFPDD copper cables



- 12x SFP+ ports for exchange connectivity
- 24x QSFPDD ports (12 port pairs) for downstream (FPGA board) connectivity
- 6x QSFPDD ports for housekeeping/management tasks or external timestamping/capture
- Configurable Layer 1 for SFP+ output
- Downstream interconnect with 2"-7" QSFPDD copper cables
- Internal tap aggregation and timestamping option with the complete LDA NeoTap features for capture and monitoring purposes.







